



WOVEN TAPE TECHNICAL DATA SHEET

Product Reference: TCB 400

Characteristics		Nominal	Tolerance	Normative	
Mass per unit area	g/m²	408	± 5%	ISO 4605	
Weave		Plain		ISO 2113	
Standard Width	mm	From 10 mm to 200 mm	± 2,5%		
Laminate Thickness	mm	0,30	± 2,5%	ISO 5084(**)	

Nominal Construction		Warp		Weft	
Fibre Description		HR Carbon Fibre 12k – 800 tex		HR Carbon Fibre 12K – 400 tex	
Thread Count	ends/cm	2,5	ISO 4602	1,3 x 2	ISO 4602
Weight Distribution	g/m² %	HR Carbon Fibre	200 50%	HR Carbon Fibre	208 50%

(**) Theorical thickness for an epoxy laminate with 40% of reinforcement in volume.

Note: Technical information furnished is based on laboratory findings and believed to be correct. No warranties of any kind are made except that the materials supplied are of standard quality. All risk and liabilities arising from handling, storage and use of products, as well as compliance with applicable legal restrictions, rests with the user.

West House | Shadsworth Business Park | off Duttons Way | Blackburn | Lancashire | BB1 2QJ

T: 01282 770666 | E: sales@cristex.co.uk | W: www.cristex.co.uk



