

WOVEN TAPE TECHNICAL DATA SHEET

Product Reference: TVU 1200



Characteristics		Nominal	Tolerance	Normative
Mass per unit area	g/m²	1249	± 5%	ISO 4605
Weave		Plain		ISO 2113
Standard Width	mm	From 10 mm to 200 mm	± 2,5%	
Laminate Thickness	mm		± 2,5%	ISO 5084(**)

Nominal Construction		Warp		Weft	
Fibre Description		Glass Roving 2400 tex		Glass Fibre EC 9 204 tex	
Thread Count	ends/cm	5,0	ISO 4602	1,2 x 2	ISO 4602
Weight Distribution	g/m² %	12k Carbon Fibre	1200 96%	Glass Fibre	49 4%

(**) Theorical thickness for an epoxy laminate with 40% of reinforcement in volume.

Note: Technical information furnished is based on laboratory findings and believed to be correct. No warranties of any kind are made except that the materials supplied are of standard quality. All risk and liabilities arising from handling, storage and use of products, as well as compliance with applicable legal restrictions, rests with the user.

West House | Shadsworth Business Park | off Duttons Way | Blackburn | Lancashire | BB1 2QJ

 $\textbf{T:} \texttt{01282} \ \texttt{770666} \ | \ \textbf{E:} \ \texttt{sales} @ \texttt{cristex.co.uk} \ | \ \textbf{W:} \ \texttt{www.cristex.co.uk} \\$

CristexItd Cristex Composites in Cristex Composite Materials