



TECHNICAL DATA SHEET

SAP No. 30007837 **Article Description** SAERcore B 450/PP25/450 1157g/m² 1250mm

Textile Structure 7007675

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)				
Layer	Construction	Areal weight	Tolerance (+/- %)	Material
3	CSM	450 g/m ²	+/- 10 %	E-Glass
2	Core	250 g/m ²	+/- 10 %	Polypropylene
1	CSM	450 g/m ²	+/- 10 %	E-Glass
Stitching		7 g/m ²	+/- 2 g/m ²	Polyamid 6.6 122 dtex

Further Characteristics					
Gauge	3.5	Stitching pattern	Tricot	Width	1250 mm
Stich length	5 mm	Total tolerance	+/- 10.1 %	Total areal weight	1157 g/m ²

- Labelling (Standard)** Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.
- Packaging (Standard)** Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.
- Storage** With original packaging: No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.
- Important advice** The Z side of the stitching line should be place preferably on the cosmetic face to obtain the best surface finish.