

TECHNICAL DATA SHEET

SAP No. 30000944 **Article Description** Q-E-820g/m²-1270mm

Textile Structure 7001689

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)				
Layer	Construction	Areal weight	Tolerance	Material
4	0 °	213 g/m ²	+/- 5 %	E-glass 600 TEX
3	45 °	200 g/m ²	+/- 5 %	E-glass 300 TEX
2	90 °	201 g/m ²	+/- 5 %	E-glass 300 TEX
1	-45°	200 g/m ²	+/- 5 %	E-glass 300 TEX
Stitching		6 g/m ²	+/- 1 g/m ²	PES (Polyester) 76 dtex

FURTHER CHARACTERISTICS					
Gauge	5,0	Stitching pattern	Tricot- warp	Width (nominal)	1270 mm
Stitch length	2.02 mm	Total tolerance	5,1 %	Total areal weight	820 g/m ²

Labelling (Standard) Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

Packaging (Standard) Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

Storage With original packaging: Temperature 15-35°C and 20-80% humidity. No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.