

TECHNICAL DATA SHEET

SAP No. 30003791 **Article Description** U-C-314g/m²-1230mm

Textile Structure 7003892

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal weight	Tolerance	Material
2	0 °	300 g/m ²	+/- 5 %	ZOLTEK PANEX 35-13 50K
1	85 °	11 g/m ²	+/- 5 %	E-glass 68 TEX
Stitching		3 g/m ²	+/- 1 g/m ²	PES (Polyester) 33 dtex SC

FURTHER CHARACTERISTICS

Gauge	5,0	Stitching pattern	Tricot	Width (nominal)	1230 mm
Stitch length	5,00 mm	Total tolerance	+/- 5,3 %	Total areal weight	314 g/m ²

Labelling (Standard)

Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

Packaging (Standard)

Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

Storage

With original packaging: Temperature 15-35°C and 20-80% humidity. No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.