

TECHNICAL DATA SHEET

SAP No. 30004044 **Article Description** U-C-603g/m²-1230mm

Textile Structure 7003743

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)				
Layer	Construction	Areal weight	Tolerance	Material
3	0 °	581 g/m ²	+/- 5 %	ZOLTEK PANEX 35-13 50K
2	-60 °	8 g/m ²	+/- 5 %	E-glass 68 TEX
1	60 °	8 g/m ²	+/- 5 %	E-glass 68 TEX
Stitching		6 g/m ²	+/- 1 g/m ²	PES (Polyester) 74 dtex SC

FURTHER CHARACTERISTICS					
Gauge	5,0	Stitching pattern	Tricot	Width (nominal)	1230 mm
Stitch length	3,00 mm	Total tolerance	+/- 5,1 %	Total areal weight	603 g/m ²

- Labelling (Standard)** Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.
- Packaging (Standard)** Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.
- Storage** With original packaging: Temperature 15-35°C and 20-80% humidity. No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.