

TECHNICAL DATA SHEET

SAP No.: 30005256 **Article Description:** 7000133

Textile Structure: Y-E-837g/m²-1270mm

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)				
Layer	Construction	Areal weight	Tolerance	Material
3	0°	425 g/m ²	+/- 5 %	E-Glass 1200 tex
2	45°	200 g/m ²	+/- 5 %	E-Glass 300 tex
1	-45°	200 g/m ²	+/- 5 %	E-Glass 300 tex
Stitching		12 g/m ²	+/- 3 g/m ²	PES (Polyester) 76 dtex

FURTHER CHARACTERISTICS					
Gauge	10,0	Stitching pattern	Tricot-warp	Width (nominal)	1,270 mm
Total tolerance	2,60 %	Total areal weight	837 g/m ²		

Labelling (Standard) Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

Packaging (Standard) Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

Storage With original packaging: Temperature 15-35°C and 20-80% humidity. No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.

Cristex Composite Materials