

TECHNICAL DATA SHEET

SAP No. 30007510

Article Description U-E-640g/m²-1260mm

Textile Structure 7004118

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)				
Layer	Construction	Areal weight	Tolerance	Material
4	0 °	567 g/m ²	+/- 5 %	E-glass 1.200 TEX
3	45 °	13 g/m ²	+/- 5 %	E-glass 68 TEX
2	90 °	35 g/m ²	+/- 5 %	E-glass 68 TEX
1	-45 °	13 g/m ²	+/- 5 %	E-glass 68 TEX
Stitching		12 g/m ²	+/- 3 g/m ²	PES (Polyester) 76 dtex

Fibre input can be determined individually

FURTHER CHARACTERISTICS					
Gauge	10,0	Stitching pattern	Tricot	Width (nominal)	1260 mm
Stitch length	3,00 mm	Total tolerance	+/- 5,4 %	Total areal weight	640 g/m ²

Labelling (Standard)

Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

Packaging (Standard)

Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

Storage

With original packaging: Temperature 15-35°C and 20-80% humidity. No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.