

TECHNICAL DATA SHEET

SAP No. 30007553

Article Description SAERflow CSM 150-BX304-445g/m²-1270mm

Textile Structure 7007999

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)				
Layer	Construction	Areal weight	Tolerance	Material
5	CSM	150 g/m ²	+/- 10 %	E-Glass
4	0°	10 g/m ²	+/- 5 %	E-Glass 34 TEX
3	45°	134 g/m ²	+/- 10 %	Synthetic 380 TEX
2	0°	10 g/m ²	+/- 5 %	E-Glass 34 TEX
1	-45 °	134 g/m ²	+/- 10 %	Synthetic 380 TEX
Stitching		7 g/m ²	+/- 2 g/m ²	Polyamide 6.6 122 dtex

FURTHER CHARACTERISTICS					
Gauge	3.5	Stitching pattern	Tricot	Width (nominal)	1270 mm
Stich length	4 mm	Total tolerance	+/- 10.1 %	Total areal weight	445 g/m ²

Labelling (Standard)

Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

Packaging (Standard)

Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

Storage

With original packaging: Temperature 15-35°C and 20-80% humidity. No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.