

## TECHNICAL DATA SHEET

**SAP No.** 30007622      **Article Description** B-E-625g/m<sup>2</sup>-1270mm

**Textile Structure** 7007696

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)				
Layer	Construction	Areal weight	Tolerance	Material
2	0°	331 g/m <sup>2</sup>	+/- 5 %	E-glass 1.200 TEX
1	90°	288 g/m <sup>2</sup>	+/- 5 %	E-glass 600 TEX
Stitching		6 g/m <sup>2</sup>	+/- 1 g/m <sup>2</sup>	PES (Polyester) 76 dtex

FURTHER CHARACTERISTICS					
Gauge	5,0	Stitching pattern	Tricot-warp	Width (nominal)	1270mm
Stitch length	3,50mm	Total tolerance	+/- 5,1 %	Total areal weight	625 g/m <sup>2</sup>

### Labelling (Standard)

Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

### Packaging (Standard)

Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

### Storage

With original packaging: Temperature 15-35°C and 20-80% humidity. No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.