

TECHNICAL DATA SHEET

SAP No. 30007785 **Article Description** SAERcore B 600/PP18/600 1387g/m² 1250mm

Textile Structure 7007830

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)				
Layer	Construction	Areal weight	Tolerance (+/- %)	Material
3	CSM	600 g/m ²	+/- 10 %	E-Glass
2	Core	180 g/m ²	+/- 10 %	Polypropylene
1	CSM	600 g/m ²	+/- 10 %	E-Glass
Stitching		7 g/m ²	+/- 2 g/m ²	Polyamid 6.6 122 dtex

Further Characteristics					
Gauge	3.5	Stitching pattern	Tricot	Width	1250 mm
Stich length	5 mm	Total tolerance	+/- 10.1 %	Total areal weight	1387 g/m ²

Labelling (Standard)

Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

Packaging (Standard)

Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

Storage

With original packaging: No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.

Important advice

The Z side of the stitching line should be placed preferably on the cosmetic face to obtain the best surface finish.