

## TECHNICAL DATA SHEET

**SAP No.** 30007907      **Article Description** B-C-406g/m<sup>2</sup>-1270mm

**Textile Structure** 7007927

### ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal weight	Tolerance	Material
2	0 °	200 g/m <sup>2</sup>	+/- 5 %	ZOLTEK PANEX 35-13 50K
1	90 °	200 g/m <sup>2</sup>	+/- 5 %	ZOLTEK PANEX 35-13 50K
Stitching		6 g/m <sup>2</sup>	+/- 1 g/m <sup>2</sup>	PES [Polyester] 76 dtex

### FURTHER CHARACTERISTICS

<b>Gauge</b>	5,0	<b>Stitching pattern</b>	tricot	<b>Width (nominal)</b>	1270 mm
<b>Stitch length</b>	2,60 mm	<b>Total tolerance</b>	+/- 5,2 %	<b>Total areal weight</b>	406 g/m <sup>2</sup>

#### Labelling (Standard)

Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

#### Packaging (Standard)

Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

#### Storage

With original packaging: Temperature 15-35°C and 20-80% humidity. No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.