

## TECHNICAL DATA SHEET

**SAP No.** 30009127      **Article Description** X-S-E-835g/m<sup>2</sup>-1270mm

**Textile Structure** 7008978

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)				
Layer	Construction	Areal weight	Tolerance	Material
4	CSM	225 g/m <sup>2</sup>	+/- 10 %	E-glass
3	45 °	301 g/m <sup>2</sup>	+/- 5 %	E-glass
2	0 °	2 g/m <sup>2</sup>	+/- 5 %	E-glass
1	-45 °	301 g/m <sup>2</sup>	+/- 5 %	E-glass
Stitching		6 g/m <sup>2</sup>	+/- 1 g/m <sup>2</sup>	Synthetic

FURTHER CHARACTERISTICS					
<b>Gauge</b>	5,0	<b>Stitching pattern</b>	warp	<b>Width (nominal)</b>	1270 mm
<b>Stitch length</b>	3,00 mm	<b>Total tolerance</b>	+/- 6.4 %	<b>Total areal weight</b>	835 g/m <sup>2</sup>

**Labelling (Standard)**      Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

**Packaging (Standard)**      Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

**Storage**      With original packaging: No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions