

## WOVEN FABRIC TECHNICAL DATA SHEET

**Product Reference:** V 210 U

Characteristics		Nominal	Tolerance	Normative
<b>Mass per unit area</b>	g/m <sup>2</sup>	223	± 5%	ISO 4605
<b>Weave</b>		Plain		ISO 2113
<b>Width</b>	mm	1000/1200	± 2,5%	
<b>Laminate thickness</b>	mm	n/a	± 5%	ISO 5084 (**)
<b>Finish</b>	Pluricompatible			
<b>Other information</b>				

Nominal Construction		Warp		Weft	
<b>Fibre Description</b>		E Glass roving 300 tex		E Glass EC 9 34 tex	
<b>Thread Count</b>	ends/cm	6,9 ends/cm	ISO 4602	4,7 ends/cm	ISO 4602
<b>Weight Distribution</b>	g/m <sup>2</sup>	Glass fibre	207	Glass fibre	16
	%		93%		7%
<b>Tensile Strength</b>	N/cm	ISO 4606		ISO 4606	

(\*\*) Theoretical thickness for an epoxy laminate with 40% of reinforcement in volume.

**Note:** Technical information furnished is based on laboratory findings and believed to be correct. No warranties of any kind are made except that the materials supplied are of standard quality. All risk and liabilities arising from handling, storage and use of products, as well as compliance with applicable legal restrictions, rests with the user.